

## SC DFR SYSTEMS SRL

### SUFLANTE CU TURBINA - PRESIUNE



Debit maxim pana la 2150 m<sup>3</sup>/h  
Presiune maxima pana la 450 mbar

[SeriaTS \(37\)](#)

#### Specificatii:

1. Rotor: Monoetajat
2. Constructie: Aluminiu
3. Debit maxim: pana la 2150 m<sup>3</sup>/h (50Hz)
4. Presiunea diferentiala Max.: 500 mbar
5. Temperatura mediului ambiant: intre -15 si +40°C
6. Motoare electrice de doi poli, monofazat si trifazat asincron, clasa de izolare F - climat tropical si clasa de protectie IP55
7. Alte accesorii sunt disponibile la cerere.

Specificatiile pot fi modificate fara notificare prealabila.

Cod	Debit max	Putere	$\Delta p$ max la 50 Hz
<a href="#">SCL-K11-TS-22.00</a>	1765 m <sup>3</sup> /h	22 kW	275 mbar
<a href="#">SCL-K11-TS-18.50</a>	1765 m <sup>3</sup> /h	18.5 kW	220 mbar
<a href="#">SCL-K11-TS-15.00</a>	1765 m <sup>3</sup> /h	15 kW	160 mbar
<a href="#">SCL-K11-TS-11.00</a>	1765 m <sup>3</sup> /h	11 kW	100 mbar
<a href="#">SCL-K10-TS-18.50</a>	1539 m <sup>3</sup> /h	18.5 kW	275 mbar
<a href="#">SCL-K10-TS-15.00</a>	1539 m <sup>3</sup> /h	15 kW	225 mbar
<a href="#">SCL-K10-TS-11.00</a>	1539 m <sup>3</sup> /h	11 kW	160 mbar
<a href="#">SCL-K09-TS-9.20</a>	1325 m <sup>3</sup> /h	9.2 kW	145 mbar
<a href="#">SCL-K09-TS-18.50</a>	1325 m <sup>3</sup> /h	18.5 kW	360 mbar
<a href="#">SCL-K09-TS-15.00</a>	1325 m <sup>3</sup> /h	15 kW	270 mbar
<a href="#">SCL-K09-TS-11.00</a>	1325 m <sup>3</sup> /h	11 kW	190 mbar

SCL-K08-TS-9.20	1007 m <sup>3</sup> /h	9.2 kW	210 mbar
SCL-K08-TS-7.50	1007 m <sup>3</sup> /h	7.5 kW	160 mbar
SCL-K08-TS-5.50	1007 m <sup>3</sup> /h	5.5 kW	100 mbar
SCL-K08-TS-15.00	1007 m <sup>3</sup> /h	15 kW	380 mbar
SCL-K08-TS-11.00	1007 m <sup>3</sup> /h	11 kW	260 mbar
SCL-K07-TS-9.20	827 m <sup>3</sup> /h	9.2 kW	275 mbar
SCL-K07-TS-7.50	827 m <sup>3</sup> /h	7.5 kW	225 mbar
SCL-K07-TS-5.50	827 m <sup>3</sup> /h	5.5 kW	150 mbar
SCL-K07-TS-11.00	827 m <sup>3</sup> /h	11 kW	350 mbar
SCL-K07-TS	827 m <sup>3</sup> /h	kW	mbar
SCL-K06-TS-7.50	563 m <sup>3</sup> /h	7.5 kW	300 mbar
SCL-K06-TS-5.50	563 m <sup>3</sup> /h	5.5 kW	200 mbar
SCL-K06-TS-4.00	563 m <sup>3</sup> /h	4 kW	130 mbar
SCL-K05-TS-4.00	409 m <sup>3</sup> /h	4 kW	250 mbar
SCL-K05-TS-3.00	409 m <sup>3</sup> /h	3 kW	175 mbar
SCL-K05-TS-2.20	409 m <sup>3</sup> /h	2.2 kW	115 mbar