

SC DFR SYSTEMS SRL

SUFLANTE CU TURBINA - VACUUM



Debit maxim pana la 2150 m³/h
Presiune maxima pana la 350 mbar

Seria TS (37)

Specificatii:

1. Rotor: dublu – intr-o treapta
 2. Constructie: Aluminiu
 3. Debit maxim: pana la 2150 m³/h (50Hz)
 4. Presiunea diferentiala Max.: 350 mbar
 5. Temperatura mediului ambiant: intre -15 si +40°C
 6. Motoare electrice de doi poli, monofazat si trifazat asincron, clasa de izolare F - climat tropical si clasa de protectie IP55
 7. Alte accesorii sunt disponibile la cerere.
- Specificatiile pot fi modificate fara notificare prealabila.

Cod	Debit max	Putere	Δp max la 50 Hz
SCL-K11-TS-22.00	1765 m ³ /h	22 kW	275 mbar
SCL-K11-TS-18.50	1765 m ³ /h	18.5 kW	220 mbar
SCL-K11-TS-15.00	1765 m ³ /h	15 kW	160 mbar
SCL-K11-TS-11.00	1765 m ³ /h	11 kW	100 mbar
SCL-K10-TS-18.50	1539 m ³ /h	18.5 kW	275 mbar
SCL-K10-TS-15.00	1539 m ³ /h	15 kW	225 mbar
SCL-K10-TS-11.00	1539 m ³ /h	11 kW	160 mbar
SCL-K09-TS-9.20	1325 m ³ /h	9.2 kW	145 mbar
SCL-K09-TS-18.50	1325 m ³ /h	18.5 kW	325 mbar
SCL-K09-TS-15.00	1325 m ³ /h	15 kW	270 mbar
SCL-K09-TS-11.00	1325 m ³ /h	11 kW	190 mbar

SCL-K08-TS-9.20	1007 m ³ /h	9.2 kW	210 mbar
SCL-K08-TS-7.50	1007 m ³ /h	7.5 kW	160 mbar
SCL-K08-TS-5.50	1007 m ³ /h	5.5 kW	100 mbar
SCL-K08-TS-15.00	1007 m ³ /h	15 kW	325 mbar
SCL-K08-TS-11.00	1007 m ³ /h	11 kW	260 mbar
SCL-K07-TS-9.20	827 m ³ /h	9.2 kW	275 mbar
SCL-K07-TS-7.50	827 m ³ /h	7.5 kW	225 mbar
SCL-K07-TS-5.50	827 m ³ /h	5.5 kW	150 mbar
SCL-K07-TS-11.00	827 m ³ /h	11 kW	300 mbar
SCL-K07-TS	827 m ³ /h	kW	mbar
SCL-K06-TS-7.50	563 m ³ /h	7.5 kW	250 mbar
SCL-K06-TS-5.50	563 m ³ /h	5.5 kW	200 mbar
SCL-K06-TS-4.00	563 m ³ /h	4 kW	130 mbar
SCL-K05-TS-4.00	409 m ³ /h	4 kW	225 mbar
SCL-K05-TS-3.00	409 m ³ /h	3 kW	175 mbar
SCL-K05-TS-2.20	409 m	2.2 kW	115 mbar