

## SC DFR SYSTEMS SRL

### SUFLANTE CU TURBINA - VACUUM



Debit maxim pana la 473 m<sup>3</sup>/h  
Presiune maxima pana la 500 mbar

Seria MD/DH (25)

#### Specificatii:

1. Rotor: dublu - doua trepte
  2. Constructie: Aluminiu
  3. Debit maxim: pana la 473 m<sup>3</sup>/h (50Hz)
  4. Presiunea diferentiala Max.: 500 mbar
  5. Temperatura mediului ambiant: intre -15 si +40°C
  6. Motoare electrice de doi poli, monofazat si trifazat asincron, clasa de izolare F - climat tropical si clasa de protectie IP55
  7. Alte accesorii sunt disponibile la cerere.
- Specificatiile pot fi modificate fara notificare prealabila.

Cod	Debit max	Putere	$\Delta p$ max la 50 Hz
SCL-K12-MD-9.20	473 m <sup>3</sup> /h	9.2 kW	350 mbar
SCL-K12-MD-7.50	473 m <sup>3</sup> /h	7.5 kW	225 mbar
SCL-K12-MD-11.00	473 m <sup>3</sup> /h	11 kW	450 mbar
SCL-K12-MD	473 m <sup>3</sup> /h	kW	mbar
SCL-K11-MD-9.20	431 m <sup>3</sup> /h	9.2 kW	500 mbar
SCL-K11-MD-7.50	431 m <sup>3</sup> /h	7.5 kW	400 mbar
SCL-K11-MD-5.50	431 m <sup>3</sup> /h	5.5 kW	250 mbar
SCL-K11-MD	431 m <sup>3</sup> /h	kW	mbar
SCL-K10-MD-7.50	387 m <sup>3</sup> /h	7.5 kW	500 mbar
SCL-K10-MD-5.50	387 m <sup>3</sup> /h	5.5 kW	340 mbar
SCL-K10-MD	387 m <sup>3</sup> /h	kW	mbar
SCL-K09-MD-7.50	311 m <sup>3</sup> /h	7.5 kW	475 mbar

SCL-K09-MD-5.50	311 m <sup>3</sup> /h	5.5 kW	425 mbar
SCL-K09-MD-4.00	311 m <sup>3</sup> /h	4 kW	285 mbar
SCL-K08R-MD-5.50	236 m <sup>3</sup> /h	5.5 kW	450 mbar
SCL-K08R-MD-4.00	236 m <sup>3</sup> /h	4 kW	375 mbar
SCL-K08R-MD-3.00	236 m <sup>3</sup> /h	3 kW	250 mbar
SCL-K07R-MD-4.00	181 m <sup>3</sup> /h	4 kW	450 mbar
SCL-K07R-MD-3.00	181 m <sup>3</sup> /h	3 kW	400 mbar
SCL-K07R-MD-2.20	181 m <sup>3</sup> /h	2.2 kW	275 mbar
SCL-40DH-2.20	140 m <sup>3</sup> /h	2.2 kW	350 mbar
SCL-30DH-1.10	100 m <sup>3</sup> /h	1.1 kW	300 mbar
SCL-20DH-0.75	70 m <sup>3</sup> /h	0.75 kW	250 mbar
SCL-15DH-0.55	50 m <sup>3</sup> /h	0.55 kW	275 mbar
SCL-10DL0.37	30 m <sup>3</sup> /h	0.37 kW	150 mbar