

## SC DFR SYSTEMS SRL

### SUFLANTE CU TURBINA - VACUUM



Debit maxim pana la 1112 m<sup>3</sup>/h  
Presiune maxima pana la 600 mbar

Seria TD (32)

#### Specificatii:

1. Rotor: dublu - doua trepte
  2. Constructie: Aluminiu (115DH este construita cu carcasa de fonta)
  3. Debit maxim: pana la 1112 m<sup>3</sup>/h (50Hz)
  4. Presiunea diferentiala Max.: 600 mbar
  5. Temperatura mediului ambiant: intre -15 si +40°C
  6. Motoare electrice de doi poli, monofazat si trifazat asincron, clasa de izolare F - climat tropical si clasa de protectie IP55
  7. Alte accesorii sunt disponibile la cerere.
- Specificatiile pot fi modificate fara notificare prealabila.

Cod	Debit max	Putere	$\Delta p$ max la 50 Hz
SCL-K11-TD-18.50	903 m <sup>3</sup> /h	18.5 kW	450 mbar
SCL-K11-TD-15.00	903 m <sup>3</sup> /h	15 kW	375 mbar
SCL-K11-TD-11.00	903 m <sup>3</sup> /h	11 kW	235 mbar
SCL-K10-TD-18.50	804 m <sup>3</sup> /h	18.5 kW	500 mbar
SCL-K10-TD-15.00	804 m <sup>3</sup> /h	15 kW	450 mbar
SCL-K10-TD-11.00	804 m <sup>3</sup> /h	11 kW	325 mbar
SCL-K09-TD-9.20	657 m <sup>3</sup> /h	9.2 kW	300 mbar
SCL-K09-TD-15.00	657 m <sup>3</sup> /h	15 kW	450 mbar
SCL-K09-TD-11.00	657 m <sup>3</sup> /h	11 kW	390 mbar
SCL-K08-TD-9.20	518 m <sup>3</sup> /h	9.2 kW	450 mbar
SCL-K08-TD-7.50	518 m <sup>3</sup> /h	7.5 kW	350 mbar
SCL-K08-TD-5.50	518 m <sup>3</sup> /h	5.5 kW	235 mbar

SCL-K08-TD	518 m <sup>3</sup> /h	kW	mbar
SCL-K07-TD-7.50	417 m <sup>3</sup> /h	7.5 kW	425 mbar
SCL-K07-TD-5.50	417 m <sup>3</sup> /h	5.5 kW	325 mbar
SCL-K07-TD	417 m <sup>3</sup> /h	kW	mbar
SCL-K06-TD-5.50	312 m <sup>3</sup> /h	5.5 kW	400 mbar
SCL-K06-TD-4.00	312 m <sup>3</sup> /h	4 kW	275 mbar
SCL-K06-TD	312 m <sup>3</sup> /h	kW	mbar
SCL-K05-TD-4.00	215 m <sup>3</sup> /h	4 kW	400 mbar
SCL-K05-TD-3.00	215 m <sup>3</sup> /h	3 kW	350 mbar
SCL-K05-TD-2.20	215 m <sup>3</sup> /h	2.2 kW	240 mbar
SCL-K04-TD-2.20	140 m <sup>3</sup> /h	2.2 kW	275 mbar
SCL-K04-TD-1.50	140 m <sup>3</sup> /h	1.5 kW	250 mbar
SCL-K04-TD-1.10	140 m <sup>3</sup> /h	1.1 kW	175 mbar