

Technical Specifications StreamLine 24000



Specifications:

• Material	:	SS 316L, according to AISI	
• Internal finish	:	Ra_{max} 0.8 μ m	
• Connections	:	3" BSP DIN2986 PN7	
• Degree of protection	:	IP 54	
• Dimensions H x W x D	:	See layout drawing	
• Weight dry	:	35 kg	- 77 lbs.
• Weight wet	:	60 kg	- 132 lbs.
• Lamp type	:	B80 VIK (one side connected)	
• Number of lamps	:	1	
• Nominal pressure	:	7 bar	- 102 PSI
• Test pressure	:	10 bar (30 minutes)	- 145 PSI

Options:

• Manual cleaning	:	see datasheet Manual Cleaning Mechanism
• UV sensor	:	see datasheet UV-sensor 4S

Customer specified items (CSI):

- Sample taps
- Tri-clamp connection
- 3" NPT connection
- Material SS 316TI

Technical Specifications StreamLine 24000



Specifications:

• Material	:	Polycarbonate		
• Colour	:	Grey		
• Degree of protection	:	IP 54		
• Dimensions H x W x D	:	180 x 254 x 111 mm	-	7.1 x 10.0 x 4.4 in.
• Weight	:	3 kg	-	7 lbs.
• Cable Cabinet - Chamber	:	2.5 m	-	8.2 ft.

Electric:

• Voltage	:	230V, 1L+N	-	230V 2L
• Frequency	:	50 Hz	-	60 Hz
• Connected power	:	90 W (±10%)		
• StreamLine control system	:	Yes (see datasheet StreamLine control system)		

Options:

- Different voltage (check person for available alternatives)

Layout drawing StreamLine 24000

